



N-Channel Enhancement-Mode Vertical DMOS FETs

Ordering Information

BV _{DSS} / BV _{DGS}	R _{DS(ON)} (max)	V _{GS(th)} (max)	Order Number / Package
			TO-236AB*
300V	25Ω	2.4V	TN2130K1

Product marking for SOT-23:
N1T*
 where * = 2-week alpha date code

*Same as SOT-23. All units shipped on 3,000 piece carrier tape reels.

Features

- Free from secondary breakdown
- Low power drive requirement
- Ease of paralleling
- Low C_{iss} and fast switching speeds
- Excellent thermal stability
- Integral Source-Drain diode
- High input impedance and high gain

Applications

- Logic level interfaces – ideal for TTL and CMOS
- Solid state relays
- Battery operated systems
- Photo voltaic drives
- Analog switches
- General purpose line drivers
- Telecom switches

Absolute Maximum Ratings

Drain-to-Source Voltage	BV _{DSS}
Drain-to-Gate Voltage	BV _{DGS}
Gate-to-Source Voltage	± 20V
Operating and Storage Temperature	-55°C to +150°C
Soldering Temperature*	300°C


* Distance of 1.6 mm from case for 10 seconds.

Advanced DMOS Technology

These enhancement-mode (normally-off) transistors utilize a vertical DMOS structure and Supertex’s well-proven silicon-gate manufacturing process. This combination produces devices with the power handling capabilities of bipolar transistors and with the high input impedance and positive temperature coefficient inherent in MOS devices. Characteristic of all MOS structures, these devices are free from thermal runaway and thermally-induced secondary breakdown.

Supertex’s vertical DMOS FETs are ideally suited to a wide range of switching and amplifying applications where high breakdown voltage, high input impedance, low input capacitance, and fast switching speeds are desired.

Package Options



Thermal Characteristics

Package	I _D (continuous)*	I _D (pulsed)	Power Dissipation @ T _A = 25°C	θ _{Jc} °C/W	θ _{ja} °C/W	I _{DR} *	I _{DRM}
TO-236AB	85mA	200mA	0.36W	200	350	85mA	200mA

* I_D (continuous) is limited by max rated T_J.


Electrical Characteristics (@ 25°C unless otherwise specified)

Symbol	Parameter	Min	Typ	Max	Unit	Conditions
BV _{DSS}	Drain-to-Source Breakdown Voltage	300			V	I _D = 1mA, V _{GS} = 0V
V _{GS(th)}	Gate Threshold Voltage	0.8		2.4	V	V _{GS} = V _{DS} , I _D = 1mA
ΔV _{GS(th)}	Change in V _{GS(th)} with Temperature			-5.5	mV/°C	I _D = 1mA, V _{GS} = V _{DS}
I _{GSS}	Gate Body Leakage			100	nA	V _{GS} = ±20V, V _{DS} = 0V
I _{DSS}	Zero Gate Voltage Drain Current			10	μA	V _{GS} = 0V, V _{DS} = Max Rating
				100	μA	V _{GS} = 0V, V _{DS} = 0.8 Max Rating T _A = 125°C
I _{D(ON)}	ON-State Drain Current	250			mA	V _{GS} = 10V, V _{DS} = 25V
R _{DS(ON)}	Static Drain-to-Source ON-State Resistance			25	Ω	V _{GS} = 4.5V, I _D = 120mA
ΔR _{DS(ON)}	Change in R _{DS(ON)} with Temperature			1.1	%/°C	V _{GS} = 4.5V, I _D = 120mA
G _{FS}	Forward Transconductance		250		mS	V _{DS} = 25V, I _D = 100mA
C _{ISS}	Input Capacitance			50	pF	V _{GS} = 0V, V _{DS} = 25V, f = 1MHz
C _{OSS}	Common Source Output Capacitance			15		
C _{RSS}	Reverse Transfer Capacitance			5		
t _{d(ON)}	Turn-ON Delay Time			10	ns	V _{DD} = 25V, I _D = 120mA R _{GEN} = 25Ω
t _r	Rise Time			7		
t _{d(OFF)}	Turn-OFF Delay Time			12		
t _f	Fall Time			15		
V _{SD}	Diode Forward Voltage Drop			1.8	V	I _{SD} = 120mA, V _{GS} = 0V
t _{rr}	Reverse Recovery Time		400		ns	I _{SD} = 120mA, V _{GS} = 0V

Notes:


- All D.C. parameters 100% tested at 25°C unless otherwise stated. (Pulse test: 300μs pulse, 2% duty cycle.)
- All A.C. parameters sample tested.

Switching Waveforms and Test Circuit




Typical Performance Curves


Output Characteristics




Saturation Characteristics




Transconductance vs. Drain Current




Power Dissipation vs. Temperature



Maximum Rated Safe Operating Area




Thermal Response Characteristics




Typical Performance Curves


BV_{DSS} Variation with Temperature




On-Resistance vs. Drain Current




Transfer Characteristics



V_{TH} and R_{DS} Variation with Temperature



Capacitance vs. Drain-to-Source Voltage



Gate Drive Dynamic Characteristics

