

Torque screwdriver - TSD 02 SAC - 1208487

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://download.phoenixcontact.com>)




Torque screwdriver, with preset torque of 0.2 Nm and 4 mm hexagonal drive for M8 connectors

The figure shows the TSD 04 SAC version

Why buy this product

- Wide range of SAC... nuts for various different applications
- The TSD-M... adapters can accommodate the various nuts
- TSD ... SAC torque screwdrivers with a range of preset torques from 0.2 Nm to 2.5 Nm
- For the TSD-M... torque screwdrivers, the torque can be custom-set

Key commercial data

Packing unit	1
Minimum order quantity	1
Catalog page	Page 292 (CL2-2011)
GTIN	 4 046356 014571
Custom tariff number	82054000
Country of origin	CZECH REPUBLIC

Technical data

General

Length (b)	205 mm
Width (a)	37 mm
Color	black
Design	Hexagonal SW4
Blade height	100 mm

Classifications

eclass

eCl@ss 4.0	21040401
eCl@ss 4.1	21040401
eCl@ss 5.0	21040401
eCl@ss 5.1	21040401

Torque screwdriver - TSD 02 SAC - 1208487

Classifications

eclass

eCl@ss 6.0	21040401
eCl@ss 7.0	21040409

etim

ETIM 2.0	EC000158
ETIM 3.0	EC000158
ETIM 4.0	EC000158

unspsc

UNSPSC 6.01	27111701
UNSPSC 7.0901	27111701
UNSPSC 11	27111701
UNSPSC 12.01	27111701
UNSPSC 13.2	27111701

Approvals

Approvals


Approvals

GOST

Ex Approvals

Approvals submitted

Approval details

GOST 

Accessories

Accessories

Tools

Torque screwdriver - TSD 02 SAC - 1208487

Accessories

Tool - SAC BIT M8-D10 - 1208461



Nut for assembling sensor/actuator cables with M8 connector and for M8 connectors with QUICKON fast connection technology, for 4 mm hexagonal drive

Tool - SACC BIT M8-D12 - 1208474



Nut for assembling SACC M8 connectors for free assembly with longitudinal knurl, excluding M8 connectors with QUICKON fast connection technology, for 4 mm hexagonal drive
