

3A, 60V Trench Schottky Rectifier

FEATURES

- Patented Trench Schottky technology
- Low power loss, high efficiency
- Ideal for automated placement
- High surge current capability
- Compliant to RoHS Directive 2011/65/EU and in accordance to WEEE 2002/96/EC
- Halogen-free according to IEC 61249-2-21 definition



DO-214AC (SMA)

MECHANICAL DATA

Case: DO-214AC (SMA)

Molding compound, UL flammability classification rating 94V-0

- Moisture sensitivity level: level 1, per J-STD-020

Packing code with suffix "G" means green compound (halogen-free)

Terminal: Matte tin plated leads, solderable per JESD22-B102

Meet JESD 201 class 2 whisker test

Polarity: Indicated by cathode band

Weight: 0.06g (approximately)

MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS (T _A =25°C unless otherwise noted)						
PARAMETER		SYMBOL	TSSA3U60		UNIT	
Marking code			A3U60			
Maximum repetitive peak reverse voltage		V _{RRM}	60		V	
Maximum average forward rectified current		I _{F(AV)}	3		A	
Peak forward surge current, 8.3 ms single half sine-wave superimposed on rated load		I _{FSM}	60		A	
			TYP.	MAX.		
Maximum instantaneous forward voltage (Note 1)	I _F = 3A	T _J = 25°C	V _F	0.48	0.54	V
		T _J = 125°C	V _F	0.41	0.50	
Maximum instantaneous reverse current at rated reverse voltage		T _J = 25°C	I _R	-	500	μA
		T _J = 125°C		12	30	mA
Typical thermal resistance		R _{θJL}	27		°C/W	
		R _{θJA}	70			
Operating temperature range		T _J	- 55 to +150		°C	
Storage temperature range		T _{STG}	- 55 to +150		°C	

Note 1: Pulse Test with Pulse Width=300μs, 1% Duty Cycle

ORDERING INFORMATION

PART NO.	PACKING CODE	PACKING CODE SUFFIX	PACKAGE	PACKING
TSSA3U60	E3	G	Clip SMA	1,800 / 7" Plastic reel
	E2		Clip SMA	7,500 / 13" Plastic reel

EXAMPLE

PREFERRED PART NO.	PART NO.	PACKING CODE	PACKING CODE SUFFIX	DESCRIPTION
TSSA3U60 E3G	TSSA3U60	E3	G	Green compound

RATINGS AND CHARACTERISTICS CURVES
($T_A=25^\circ\text{C}$ unless otherwise noted)

FIG.1 FORWARD CURRENT DERATING CURVE




FIG. 2 TYPICAL FORWARD CHARACTERISTICS




FIG. 3 TYPICAL REVERSE CHARACTERISTICS




FIG.4 TYPICAL JUNCTION CAPACITANCE






FIG. 5 MAXIMUM NON-REPETITIVE FORWARD SURGE CURRENT




PACKAGE OUTLINE DIMENSIONS
DO-214AC (SMA)



Dim.	Unit(mm)		Unit(inch)	
	Min	Max	Min	Max
A	1.27	1.58	0.05	0.062
B	4.06	4.6	0.16	0.181
C	2.29	2.84	0.09	0.111
D	1.99	2.5	0.078	0.098
E	0.9	1.41	0.035	0.056
F	4.95	5.33	0.195	0.21
G	0.1	0.2	0.004	0.008
H	0.15	0.31	0.006	0.012

SUGGESTED PAD LAYOUT



Symbol	Unit (mm)	Unit (inch)
A	1.68	0.066
B	1.52	0.060
C	3.93	0.155
D	2.41	0.095
E	5.45	0.215

MARKING DIAGRAM



P/N = Marking Code
 G = Green Compound
 YW = Date Code
 F = Factory Code

Notice

Specifications of the products displayed herein are subject to change without notice. TSC or anyone on its behalf, assumes no responsibility or liability for any errors or inaccuracies.

Information contained herein is intended to provide a product description only. No license, express or implied, to any intellectual property rights is granted by this document. Except as provided in TSC's terms and conditions of sale for such products, TSC assumes no liability whatsoever, and disclaims any express or implied warranty, relating to sale and/or use of TSC products including liability or warranties relating to fitness for a particular purpose, merchantability, or infringement of any patent, copyright, or other intellectual property right.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications. Customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify TSC for any damages resulting from such improper use or sale.