



TRIACS

DESCRIPTION

Glass passivated triacs in a plastic envelope, intended for use in applications requiring highbidirectional transient and blocking voltage capability and high thermal cycling performance. Typical applications include motor control, industrial and domestic lighting, heating and static switching.

SYMBOL



1:MT1 2:MT2 3:GATE

ABSOLUTE MAXIMUM RATINGS

PARAMETER	SYMBOL	RATINGS	UNIT
Repetitive peak off-state voltages UT134F/G-5 UT134F/G-6 UT134F/G-8	$V_{DRM}$	500 600* 800	V
RMS on-state current full sine wave; $T_{mb} \leq 107\text{ }^{\circ}\text{C}$	$I_{T(RMS)}$	4	A
Non-repetitive peak on-state current (Full sine wave; $T_j = 25\text{ }^{\circ}\text{C}$ prior to surge) $t = 20\text{ms}$ $t = 16.7\text{ ms}$	$I_{TSM}$	25 27	A
$I^2t$ for fusing $t = 10\text{ ms}$	$I^2t$	3.1	$\text{A}^2\text{s}$
Repetitive rate of rise of on-state current after triggering $I_{TM} = 6\text{ A}$ ; $I_G = 0.2\text{A}$ ; $dI_G/dt = 0.2\text{A}/\mu\text{s}$ T2+ G+ T2+ G- T2- G- T2- G+	$dI_T/dt$	50 50 50 10	$\text{A}/\mu\text{s}$
Peak gate voltage	$V_{GM}$	5	V
Peak gate current	$I_{GM}$	2	A
Peak gate power	$P_{GM}$	5	W
Average gate power (over any 20 ms period)	$P_{G(AV)}$	0.5	W
Storage temperature	$T_{stg}$	-40 ~ 150	$^{\circ}\text{C}$
Operating junction temperature	$T_j$	125	$^{\circ}\text{C}$

\*Although not recommended, off-state voltages up to 800V may be applied without damage, but the traic may switch to the on-state. The rate of rise of current should not exceed 3A/μs.

THERMAL RESISTANCES

PARAMETER	SYMBOL	MIN	TYP	MAX	UNIT
Thermal resistance Junction to mounting base Full cycle Half cycle	R <sub>th j-mb</sub>			3.0 3.7	K/W K/W
			100		K/W
Thermal resistance Junction to ambient (In free air)	R <sub>th j-a</sub>		100		K/W

STATIC CHARACTERISTICS (T<sub>j</sub>=25°C, unless otherwise stated)

PARAMETER	SYMBOL	CONDITIONS	MIN	TYP	MAX		UNIT
					UT134F	UT134G	
Gate trigger current	I <sub>GT</sub>	V <sub>D</sub> = 12 V; I <sub>T</sub> = 0.1 A T2+ G+ T2+ G- T2- G- T2- G+		5	25	50	mA
				8	25	50	
				11	25	50	
				30	70	100	
Latching current	I <sub>L</sub>	V <sub>D</sub> = 12 V; I <sub>GT</sub> = 0.1 A T2+ G+ T2+ G- T2- G- T2- G+		7	20	30	mA
				16	30	45	
				5	20	30	
				7	30	45	
Holding current	I <sub>H</sub>	V <sub>D</sub> = 12 V; I <sub>GT</sub> = 0.1 A		5	15	30	mA
On-state voltage	V <sub>T</sub>	I <sub>T</sub> = 5 A		1.4	1.7		V
Gate trigger voltage	V <sub>GT</sub>	V <sub>D</sub> = 12 V; I <sub>T</sub> = 0.1 A		0.7	1.5		V
		V <sub>D</sub> = 400V ; I <sub>T</sub> = 0.1 A; T <sub>j</sub> = 125°C	0.25	0.4			V
Off-state leakage current	I <sub>D</sub>	V <sub>D</sub> = V <sub>DRM(max)</sub> ; T <sub>j</sub> = 125 °C		0.1	0.5		mA

DYNAMIC CHARACTERISTICS (T<sub>j</sub>=25°C, unless otherwise stated)

PARAMETER	SYMBOL	CONDITIONS	MIN		TYP	MAX	UNIT
			UT134F	UT134G			
Critical rate of rise of Off-state voltage	dV <sub>D</sub> /dt	V <sub>DM</sub> = 67% V <sub>DRM(max)</sub> ; T <sub>j</sub> = 125°C; exponential waveform; gate open circuit	50	200	250		V/μs
Critical rate of change of Commutating voltage	dV <sub>com</sub> /dt	V <sub>DM</sub> =400V; T <sub>j</sub> =95°C; I <sub>T(RMS)</sub> =4A; dI <sub>com</sub> /dt = 1.8A/ms; gate open circuit		10	50		V/μs
Gate controlled turn-on time	t <sub>gt</sub>	I <sub>TM</sub> = 6 A; V <sub>D</sub> = V <sub>DRM(max)</sub> ; I <sub>G</sub> =0.1A; dI <sub>G</sub> /dt=5A/μs			2		μs

TYPICAL CHARACTERISTICS




Fig.1. Maximum on-state dissipation,  $P_{tot}$ , versus rms on-state current,  $I_{T(RMS)}$  where  $\alpha$  = conduction angle.




Fig.4. Maximum permissible rms current  $I_{T(RMS)}$ , versus mounting base temperature  $T_{mb}$




Fig.2. Maximum Permissible non-repetitive peak on-state Current  $I_{TSM}$ , versus pulse width  $t_p$  for sinusoidal currents,  $t_p \leq 20ms$




Fig. 5. Maximum permissible repetitive rms on-state current  $I_{T(RMS)}$ , versus surge duration, for sinusoidal currents,  $f=50Hz$ ;  $T_{mb} \leq 107^\circ C$




Fig.3. Maximum Permissible non-repetitive peak on-state current  $I_{TSM}$ , versus number of cycles, for sinusoidal currents,  $f=50Hz$ .




Fig.6. Normalised gate trigger voltage  $V_{GT}(T_j)/V_{GT}(25^\circ C)$ , versus junction temperature  $T_j$




Fig. 7. Normalised gate trigger Current  $I_{GT}(T_j)/I_{GT}(25^\circ\text{C})$ , versus junction temperature  $T_j$




Fig. 10. Typical and maximum on-state characteristic.




Fig. 8. Normalised latching Current  $I_L(T_j)/I_L(25^\circ\text{C})$ , versus junction temperature  $T_j$




Fig. 11. Transient thermal impedance  $Z_{thj-mb}$ , versus pulse width  $t_p$ .




Fig. 9. Normalised holding current  $I_H(T_j)/I_H(25^\circ\text{C})$ , versus junction temperature  $T_j$




Fig. 12. Typical commutation  $dV/dt$  versus junction temperature, parameter commutation  $dI/dt$ . The triac should commute when the  $dV/dt$  is below the value on the appropriate curve for pre-commutation  $dI/dt$

UTC assumes no responsibility for equipment failures that result from using products at values that exceed, even momentarily, rated values (such as maximum ratings, operating condition ranges, or other parameters) listed in products specifications of any and all UTC products described or contained herein. UTC products are not designed for use in life support appliances, devices or systems where malfunction of these products can be reasonably expected to result in personal injury. Reproduction in whole or in part is prohibited without the prior written consent of the copyright owner. The information presented in this document does not form part of any quotation or contract, is believed to be accurate and reliable and may be changed without notice.