## XZCP0566L5

pre-wired connectors XZ - straight female - M8 - 3 pins - cable PUR 5m





Main	
Accessory / separate part category	Cabling accessory
Accessory / separate part type	Pre-wired connectors
Series name	General purpose

### Complementary

Complementary		
Electrical connection	Straight female connector M8, 3 pins	
Cable connector fixing	Screw-on	
Collar material	Metal	
Status LED	Without	
Cable length	5 m	
Cable outer diameter	5.2 mm	
Cable composition	3 x 0.34 mm²	
Wire insulation material	PUR	
[Ue] rated operational voltage	60 V AC 75 V DC	
[In] rated current	4 A	
Contact resistance	5000 μOhm	
Minimum insulating resistance	1 GΩ	
Net weight	0.12 kg	

#### **Environment**

Environment		
IP degree of protection	IP65 IP67 IP69K	
Product certifications	CULus	
Ambient air temperature for operation	-4080 °C static -580 °C flexing	
Ambient air temperature for storage	-4080 °C	

### **Packing Units**

Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Weight	128 g	
Package 1 Height	3.9 cm	
Package 1 width	25 cm	
Package 1 Length	27.8 cm	
Unit Type of Package 2	BAG	
Number of Units in Package 2	1	
Package 2 Weight	128 g	

Package 2 Height	3.9 cm
Package 2 width	25 cm
Package 2 Length	27.8 cm
Unit Type of Package 3	S02
Number of Units in Package 3	20
Package 3 Weight	2.852 kg
Package 3 Height	15 cm
Package 3 width	30 cm
Package 3 Length	40 cm

### Offer Sustainability

Sustainable offer status	Green Premium product
REACh Regulation	☐ REACh Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EEU RoHS  Declaration
Mercury free	Yes
RoHS exemption information	₫Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information


### Contractual warranty

Warranty	18 months

# Product data sheet Dimensions Drawings

## XZCP0566L5


### **Dimensions**



L: Lenght of cable

### **Connections and Schemes**

### Connector



BU : Blue BN : Brown BK : Black