

ZXCT1050

Precision wide input range current monitor

Description


The ZXCT1050 is a wide input range current monitor, which operates over a range of input voltages from ground up to $V_{CC}-2V$. As a result the ZXCT1050 can be used on the high or low side of the load.

The ZXCT1050 provides variable gain by using two external resistors. The first of which sets the transconductance and the second setting the overall gain.

Features

- Accurate down to end current sensing
- Output voltage scaling x10
- 0 to $V_{CC}-2V$ sense input range
- 2.7 to 20V supply range
- 50 μ A quiescent current
- SOT23-5 package

Pin connections




The very low offset voltage enables a typical accuracy of 1% for sense voltages of only 30mV, giving better tolerances for small sense resistors necessary at higher currents.

Applications

- Power supply
- DC motor and solenoid control
- Battery management
- Over current monitor
- Power management
- Short circuit detection

Typical application circuit



Ordering information

| Order code | Pack | Part mark | Reel size (inches) | Tape width (mm) | Quantity per reel |
|--------------|---------|-----------|--------------------|-----------------|-------------------|
| ZXCT1050E5TA | SOT23-5 | 1050 | 7 | 8 | 3000 |

Absolute maximum ratings

| | |
|---|---|
| V_{CC} max. | 20V |
| Voltage on SENSE- and SENSE+ | -0.6 to V_{CC} |
| Voltage on all other pins | -0.6V and $V_{CC} + 0.6V$ |
| $V_{SENSE} = (V_{SENSE+}) - (V_{SENSE-})$ | 500mV |
| Operating temperature | -40 to 125°C |
| Storage temperature | -55 to 150°C |
| Maximum junction temperature | 150°C |
| Package power dissipation | 300mW* at $T_A = 25^\circ\text{C}$ (De-rate to zero for $T_J = 150^\circ\text{C}$) |

Operation above the absolute maximum rating may cause device failure. Operation at the absolute maximum ratings, for extended periods, may reduce device reliability.

Recommended operating conditions

| Parameter | | Min. | Max. | Units |
|--------------|--|------|------------|-------|
| V_{SENSE+} | Common-mode sense input range | 0 | $V_{CC}-2$ | V |
| V_{CC} | Supply voltage range | 2.7 | 20 | V |
| V_{SENSE} | Differential sense input voltage range | 10 | 300 | mV |
| V_{OUT} | Output voltage range | 0 | $V_{CC}-2$ | V |
| T_A | Ambient temperature range | -40 | 125 | °C |

Recommended resistor gain setting combinations

| Gain | R_{SH} | R_G |
|------|----------------|----------------|
| 10 | 7.5k Ω | 3.75k Ω |
| 20 | 7.5k Ω | 7.5k Ω |
| 50 | 7.5k Ω | 18.7k Ω |
| 100 | 7.5k Ω | 37.5k Ω |
| 20 | 3.75k Ω | 3.75k Ω |
| 50 | 1.5k Ω | 3.75k Ω |
| 100 | 750 Ω | 3.75k Ω |

Pin function table

| PIN | Name | Description |
|-----|----------|---|
| 1 | V_{CC} | This is the analog supply and provides power to internal circuitry. |
| 2 | GND | Ground pin. |
| 3 | OUT | Output pin. A resistor, R_{GAIN} , connected from this pin pin down to ground develops an output voltage. |
| 4 | SENSE+ | This is the positive input of the current monitor and has an input range from 0V up to $V_{CC} - 2V$. |
| 5 | SENSE- | This is the negative input of the current monitor and has an input range from 0V up to $V_{CC} - 2V$. The current through this pin varies with differential sense voltage. A resistor, R_{SHUNT} , from this pin to the rail being sensed set the transconductance of the current monitor. |

ZXCT1050

Electrical characteristics

Test conditions $T_A = 25^\circ\text{C}$, $V_{\text{SENSE}+} = 10\text{V}$, $V_{\text{CC}} = 12\text{V}$, $V_{\text{SENSE}} = 100\text{mV}$, $R_{\text{SH}} = 7.5\text{k}\Omega$, $R_{\text{G}} = 3.75\text{k}\Omega$.







| Symbol | Parameter | Conditions | Min. | Typ. | Max. | Units | |
|---------------------|---|---|--|--------------------------|---------------------------|-----------------------|-----|
| I_Q | V_{CC} pin current | $V_{\text{SENSE}} = 0\text{V}$ | | 45 | 70 | μA | |
| V_{OUT} | Output voltage | $V_{\text{SENSE}} = 0\text{V}$ =30mV =100mV =150mV | 0 285 0.97 1.45 | 3 300 1.00 1.50 | 15 315 1.03 1.55 | mV mV V V | |
| $I_{\text{SENSE}+}$ | $V_{\text{SENSE}+}$ input current | $V_{\text{SENSE}} = 0\text{V}$ | | 60 | 150 | nA | |
| $I_{\text{SENSE}-}$ | $V_{\text{SENSE}-}$ input current | $V_{\text{SENSE}} = 0\text{V}$ | | 15 | 150 | nA | |
| $V_{\text{OUT TC}}$ | V_{OUT} variation with temperature | See note (*) | | | 300 | ppm/ $^\circ\text{C}$ | |
| Gain | $V_{\text{OUT}}/V_{\text{SENSE}}$ | | | 10 | | | |
| Accuracy | Total output error | | -3 | | 3 | % | |
| BW | Bandwidth | $V_{\text{SENSE}(\text{DC})} = 10\text{mV}$ | $V_{\text{SENSE}(\text{AC})} = 10\text{mV}_{\text{PP}}$ CL = 5pF, | | 300 | | kHz |
| | | $V_{\text{SENSE}(\text{DC})} = 100\text{mV}$ | | | 0.8 | | MHz |
| PSRR | Power supply rejection ratio | $V_{\text{CC}} = 2.7\text{V to } 20\text{V}$ $V_{\text{SENSE}+} = 0.7\text{V}$ | | 60 | | dB | |
| CMRR | Common mode rejection ratio | $V_{\text{CC}} = 20\text{V}$ $V_{\text{SENSE}+} = 0 \text{ to } 18\text{V}$ | | 70 | | dB | |

NOTES:

(*) Temperature dependent measurements are extracted from characterisation and simulation results.







Typical characteristics

$R_G = 3.75k\Omega$, $R_{SH} = 7.5k\Omega$ unless otherwise stated.




Typical characteristics

$R_G = 3.75k\Omega$, $R_{SH} = 7.5k\Omega$ unless otherwise stated.




Typical characteristics


$R_G = 3.75k\Omega$, $R_{SH} = 7.5k\Omega$ unless otherwise stated.




Small Signal Frequency Response




CMRR



PSRR



Large Signal Step Response



Small Signal Step Response


Referred to 1V

Applications information

The ZXCT1050 is a current output version of the ZXCT1051 and as such uses a separate power supply pin. All biasing for the internal amplifiers comes from its separate V_{CC} input and is not 'line powered', unlike the ZXCT1021.

This means that at very small sense voltages the ZXCT1050 draws very little current ($<1\mu\text{A}$) from the lines being sensed.

The separate V_{CC} pin enables the ZXCT1050 to be operated at sense line voltages down to 0V, where the ZXCT1021 would switch off. This feature enables the ZXCT1050 to be used to sense the currents flowing through lines that have been shorted to ground.



Basic operation

Load current, I_L , from V_{RAIL} is drawn through R_{SENSE} developing a voltage V_{SENSE} across the sense inputs of the ZXCT1050.

The internal amplifier forces V_{SENSE} across external resistance R_{SH} (internal on the ZXCT1051) causing a current to flow through transistor Q1 and out of the output pin, OUT. This current is then converted to a voltage by a resistor, R_G , between OUT and GND.

The overall gain of the ZXCT1050 is determined by the following expression:

$$\text{GAIN} = 20 \times \frac{R_G}{R_{SH}}$$

A ratio of 1:2 between R_{SH} and R_G creates the fixed gain of 10 with an output impedance equal to R_G (see electrical characteristics for output current-voltage characteristics).

The ZXCT1050 has both R_G and R_{SH} external. This allows R_G and R_{SH} to be varied so that the required gain can be achieved at the required output impedance.

For low power applications both R_G and R_{SH} can be increased whereas for driving low impedance R_G and R_{SH} can be decreased.

The maximum recommended value for R_G is 40k Ω and the maximum recommended value for R_{SH} is 10k Ω . Large values of R_{SH} start increasing the effective input offset error, while large values of R_G can create load errors and reduce bandwidths.


The maximum differential input voltage, V_{SENSE} , is 150mV ($I_L * R_{SENSE}$); however voltages up to 500mV will not damage it. This can be increased further by the inclusion of a resistor, R_{LIM} , between the SENSE+ pin and the rail being sensed, V_{RAIL} .

For best performance R_{SENSE} should be connected as close to the SENSE+ and SENSE- pins thus minimizing any series resistance with R_{SENSE} .

Intentionally left blank

ZXCT1050

Package outline - SOT23-5



| DIM | Millimeters | | Inches | |
|-----|-------------|------|------------|--------|
| | Min. | Max. | Min. | Max. |
| A | - | 1.00 | - | 0.0393 |
| A1 | 0.01 | 0.10 | 0.0003 | 0.0039 |
| A2 | 0.84 | 0.90 | 0.0330 | 0.0354 |
| b | 0.30 | 0.45 | 0.0118 | 0.0177 |
| c | 0.12 | 0.20 | 0.0047 | 0.0078 |
| D | 2.90 BSC | | 0.114 BSC | |
| E | 2.80 BSC | | 0.110 BSC | |
| E1 | 1.60 BSC | | 0.062 BSC | |
| e | 0.95 BSC | | 0.0374 BSC | |
| e1 | 1.90 BSC | | 0.0748 BSC | |
| L | 0.30 | 0.50 | 0.0118 | 0.0196 |
| L2 | 0.25 BSC | | 0.010 BSC | |
| a° | 4° | 12° | 4° | 12° |

Note: Controlling dimensions are in millimeters. Approximate dimensions are provided in inches

Definitions

Product change

Zetex Semiconductors reserves the right to alter, without notice, specifications, design, price or conditions of supply of any product or service. Customers are solely responsible for obtaining the latest relevant information before placing orders.

Applications disclaimer

The circuits in this design/application note are offered as design ideas. It is the responsibility of the user to ensure that the circuit is fit for the user's application and meets with the user's requirements. No representation or warranty is given and no liability whatsoever is assumed by Zetex with respect to the accuracy or use of such information, or infringement of patents or other intellectual property rights arising from such use or otherwise. Zetex does not assume any legal responsibility or will not be held legally liable (whether in contract, tort (including negligence), breach of statutory duty, restriction or otherwise) for any damages, loss of profit, business, contract, opportunity or consequential loss in the use of these circuit applications, under any circumstances.

Life support

Zetex products are specifically not authorized for use as critical components in life support devices or systems without the express written approval of the Chief Executive Officer of Zetex Semiconductors plc. As used herein:

A. Life support devices or systems are devices or systems which:

1. are intended to implant into the body

or

2. support or sustain life and whose failure to perform when properly used in accordance with instructions for use provided in the labelling can be reasonably expected to result in significant injury to the user.

B. A critical component is any component in a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or to affect its safety or effectiveness.

Reproduction

The product specifications contained in this publication are issued to provide outline information only which (unless agreed by the company in writing) may not be used, applied or reproduced for any purpose or form part of any order or contract or be regarded as a representation relating to the products or services concerned.

Terms and Conditions

All products are sold subjects to Zetex' terms and conditions of sale, and this disclaimer (save in the event of a conflict between the two when the terms of the contract shall prevail) according to region, supplied at the time of order acknowledgement.

For the latest information on technology, delivery terms and conditions and prices, please contact your nearest Zetex sales office.

Quality of product

Zetex is an ISO 9001 and TS16949 certified semiconductor manufacturer.

To ensure quality of service and products we strongly advise the purchase of parts directly from Zetex Semiconductors or one of our regionally authorized distributors. For a complete listing of authorized distributors please visit: www.zetex.com/salesnetwork

Zetex Semiconductors does not warrant or accept any liability whatsoever in respect of any parts purchased through unauthorized sales channels.

ESD (Electrostatic discharge)

Semiconductor devices are susceptible to damage by ESD. Suitable precautions should be taken when handling and transporting devices. The possible damage to devices depends on the circumstances of the handling and transporting, and the nature of the device. The extent of damage can vary from immediate functional or parametric malfunction to degradation of function or performance in use over time. Devices suspected of being affected should be replaced.

Green compliance

Zetex Semiconductors is committed to environmental excellence in all aspects of its operations which includes meeting or exceeding regulatory requirements with respect to the use of hazardous substances. Numerous successful programs have been implemented to reduce the use of hazardous substances and/or emissions.

All Zetex components are compliant with the RoHS directive, and through this it is supporting its customers in their compliance with WEEE and ELV directives.

Product status key:

| | |
|-----------------------------------|--|
| "Preview" | Future device intended for production at some point. Samples may be available |
| "Active" | Product status recommended for new designs |
| "Last time buy (LTB)" | Device will be discontinued and last time buy period and delivery is in effect |
| "Not recommended for new designs" | Device is still in production to support existing designs and production |
| "Obsolete" | Production has been discontinued |

Datasheet status key:

| | |
|-----------------------|---|
| "Draft version" | This term denotes a very early datasheet version and contains highly provisional information, which may change in any manner without notice. |
| "Provisional version" | This term denotes a pre-release datasheet. It provides a clear indication of anticipated performance. However, changes to the test conditions and specifications may occur, at any time and without notice. |
| "Issue" | This term denotes an issued datasheet containing finalized specifications. However, changes to specifications may occur, at any time and without notice. |

Zetex sales offices

| Europe | Americas | Asia Pacific | Corporate Headquarters |
|--|---|--|--|
| Zetex GmbH Kustermann-park Balanstraße 59 D-81541 München Germany Telephone: (49) 89 45 49 49 0 Fax: (49) 89 45 49 49 49 europe.sales@zetex.com | Zetex Inc 700 Veterans Memorial Highway Hauppauge, NY 11788 USA Telephone: (1) 631 360 2222 Fax: (1) 631 360 8222 usa.sales@zetex.com | Zetex (Asia Ltd) 3701-04 Metroplaza Tower 1 Hing Fong Road, Kwai Fong Hong Kong Telephone: (852) 26100 611 Fax: (852) 24250 494 asia.sales@zetex.com | Zetex Semiconductors plc Zetex Technology Park, Chadderton Oldham, OL9 9LL United Kingdom Telephone: (44) 161 622 4444 Fax: (44) 161 622 4446 hq@zetex.com |

© 2007 Published by Zetex Semiconductors plc